

TYCHO HEPA Series

| | |
|--------------------|--|
| Series: | DHF- HV - GI |
| Class: | H10 to H14 : EN1822 |
| Media: | Microglass fibre minipleated media |
| Seperators: | EVA-based hotmelt |
| Adhesive: | EVA-based hotmelt |
| Gasket: | Single piece neoprene foam |
| Market: | Food & Beverage Industrial Pharma/Cleanroom |



Description

General use multi V HEPA filter, suitable for high volume flow rates (4000 m³/hr). Filter is made with microglass media in a minipleat form and shaped in a multi “V” format to ensure optimum pressure drop.

A single piece neoprene foam gasket ensures a 100% leak free contact. Galvanised steel frame has 2 No. plastic handles for easy lifting. Media packs are sealed into the entire frame using a hot melt adhesive.

Technical Details

| Grade | Width | Height | Depth | Surface Area | Airflow | Pa Clean | T° max |
|--------|-------|--------|-------|----------------|-------------------|----------|---------|
| EN1822 | mm | mm | mm | M ² | M ³ /s | | Celsius |
| H10 | 610mm | 610mm | 290mm | 35 | 5000 | 235 | 80 |
| H10 | 610mm | 610mm | 290mm | 21 | 4000 | 235 | 80 |
| H10 | 305mm | 610mm | 290mm | 14 | 2000 | 235 | 80 |
| H12 | 610mm | 610mm | 290mm | 40 | 4000 | 257 | 80 |
| H12 | 610mm | 610mm | 290mm | 33 | 3400 | 257 | 80 |
| H12 | 305mm | 610mm | 290mm | 16 | 1500 | 257 | 80 |
| H13 | 610mm | 610mm | 290mm | 40 | 4000 | 257 | 80 |
| H13 | 610mm | 610mm | 290mm | 33 | 3400 | 257 | 80 |
| H13 | 305mm | 610mm | 290mm | 16 | 1500 | 257 | 80 |
| H14 | 610mm | 610mm | 290mm | 40 | 4000 | 307 | 80 |
| H14 | 305mm | 610mm | 290mm | 16 | 1500 | 307 | 80 |

Contact Details

Delta Filtration, Kilmallock Business Park, Kilmallock, Co. Limerick, Ireland

Tel : +353 63 98829 | Fax : +353 63 98830 | E-mail : info@deltafiltration.com | Web : www.deltafiltration.com